



ART. 1670035

Control equipment for centralized lubrication system

Control and management unit 12/24 V DC for air operated pump s. C15F - C30F with air operated discharge valve and motor operated pump s. C15B18 - C30B15 - C30B18 with electromagnetic discharge valve



FLUIDS

FRESH OIL | GREASE

SECTORS

AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE
FRESH OIL | GREASE

Features	UM	Value
Suitable for pump		C15F, C15B18, C20F, C30F, C30B15, C30B18
Voltage		12/24 V DC
Power consumed		200
Inlet		9
Outlet		5
Protection rating		IP64
Working temperature		-25 ÷ +60
Packing	N° - m ³	1 - 0,005
Net weight	kg	1,2 ÷ 1,4
Gross weight	kg	1,1 ÷ 1,3

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2018 All rights reserved to RAASM S.p.A.