



TIEFFE S.P.A. con socio unico

soggetta a direzione e coordinamento da parte di Hydro Holding S.p.A.

Sede legale: 27010 - Cura Carpignano (PV) Via Dell'Industria n. 7

Codice Fiscale e n° Iscrizione Registro Imprese di Pavia: 06256260966

Capitale Sociale: Euro 3.330.000= I.V.

Tel: +39 0382 583020 Fax: +39 0382 483314

WEB: www.tieffe.com

E-MAIL: tieffe@tieffe.com

Cura Carpignano 22-02-2016

FROM: TIEFFE S.P.A.

TO: ALL CUSTOMERS

OBJECT: NEW NO-SKIVE FERRULES – “BSN4xxA” SERIES

Dear Customer,

here we would like to send you the information about the new “**BSN4xxA**” SERIES:

- New “**BSN4xxA**” range is an updating of present “**BSN4xx**” range
- These ferrules are dedicated to “CS” insert type. They can't be used on “CX” or “CH” inserts
- Crimping diameters are different from the previous range “BSN4xx”

The “BSN4xx” range will be available until stocks are exhausted, then orders will be confirmed on new range “BSN4xxA”.

Following we send you the technical information of the new items.


We want to remember that the swaging diameter value is only a reference and it depends also of the hose supplier. For this reason we suggest to test the internal collapse of the insert with its Control pin.

For every doubt don't hesitate to contact our Sales Service.

Best regards

TIEFFE S.P.A.

NO-SKIVE



NO-SKIVE

BSN4--A

RUBBER HOSES STEEL WIRE SPIRAL - TUBI GOMMA SPIRALATI ACCIAIO

Hose Size			ISO 3862 4SP			ISO 3862 4SH			ISO 3862 R12 SAE100 R12			ISO 3862 R13 SAE100 R13			ISO 3862 R15 SAE100 R15			Collapse control mandrel Spina controllo collasso			
			Ferrule Boccola	Skiving length Lungh. di pelatura	Ø Swage (Ref.) Ø Press. (Rif.)	Ferrule Boccola	Skiving length Lungh. di pelatura	Ø Swage (Ref.) Ø Press. (Rif.)	Ferrule Boccola	Skiving length Lungh. di pelatura	Ø Swage (Ref.) Ø Press. (Rif.)	Ferrule Boccola	Skiving length Lungh. di pelatura	Ø Swage (Ref.) Ø Press. (Rif.)	Ferrule Boccola	Skiving length Lungh. di pelatura	Ø Swage (Ref.) Ø Press. (Rif.)		Ferrule Boccola	Skiving length Lungh. di pelatura	Ø Swage (Ref.) Ø Press. (Rif.)
DN	Inch	Dash	Part.N.	mm	mm	Part.N.	mm	mm	Part.N.	mm	mm	Part.N.	mm	mm	Part.N.	mm	mm	Part.N.	mm	mm	Part.N.
19	3/4"	-12	BSN412A	no-skive	37,4	BSN412A	no-skive	37,5	BSN412A	no-skive		BSN412A	no-skive	37,8	BSN412A	no-skive					SCS12
25	1"	-16	BSN416A	no-skive	44,0	BSN416A	no-skive	44,0	BSN416A	no-skive		BSN416A	no-skive	44,3	BSN416A	no-skive					SCS16
31,5	1 1/4"	-20				BSN420A	no-skive	52,5	BSN420A	no-skive	53,4										SCS20
38	1 1/2"	-24				BSN424A	no-skive	60,0	BSN424A	no-skive	60,9										SCS24
51	2"	-32				BSN432A	no-skive	75,6	BSN432A	no-skive	75,9										SCS32

For R15 data, contact TIEFFE.

Per applicazioni R15 contattare la TIEFFE.

The crimping diameter shown in the chart are only as reference

I diametri di pressatura mostrati in tabella sono puramente indicativi