

SPRAY PERFORMANCE

CAPACITY SIZE	SPRAY ANGLE AT 40 PSI				CAPACITY G.P.M. (GALLONS PER MINUTE)							CAPACITY (LITERS PER MINUTE)					
	0°	15°	25°	40°	1000 PSI	1500 PSI	2000 PSI	2500 PSI	3000 PSI	3500 PSI	4000 PSI	70 Bar	100 Bar	150 Bar	200 Bar	250 Bar	275 Bar
02	✓	✓	✓	✓	1.0	1.2	1.4	1.6	1.7	1.9	2.0	3.8	4.6	5.6	6.4	7.3	7.7
03	✓	✓	✓	✓	1.5	1.8	2.1	2.4	2.6	2.8	3.0	5.7	6.8	8.4	9.7	10.7	11.3
035	✓	✓	✓	✓	1.8	2.2	2.5	2.8	3.1	3.3	3.5	6.7	8.0	9.8	11.3	12.5	13.2
04	✓	✓	✓	✓	2.0	2.5	2.8	3.2	3.5	3.7	4.0	7.6	9.1	11.2	12.9	14.4	15.1
045	✓	✓	✓	✓	2.3	2.8	3.2	3.6	3.9	4.2	4.5	8.6	10.3	12.6	14.5	16.2	17.0
05	✓	✓	✓	✓	2.5	3.1	3.5	4.0	4.3	4.7	5.0	9.5	11.4	14.0	16.1	18.0	18.9
055	✓	✓	✓	✓	2.8	3.4	3.9	4.3	4.8	5.1	5.5	10.5	12.5	15.4	17.7	19.8	21
06	✓	✓	✓	✓	3.0	3.7	4.2	4.7	5.2	5.6	6.0	11.4	13.7	16.7	19.3	22	23
065	✓	✓	✓	✓	3.3	4.0	4.6	5.1	5.6	6.1	6.5	12.4	14.8	18.1	21	23	25
07	✓	✓	✓	✓	3.5	4.3	4.9	5.5	6.1	6.5	7.0	13.3	16.0	19.5	23	25	26
075	✓	✓	✓	✓	3.8	4.6	5.3	5.9	6.5	7.0	7.5	14.3	17.1	21	24	27	28
08	✓	✓	✓	✓	4.0	4.9	5.7	6.3	6.9	7.5	8.0	15.3	18.2	22	26	29	30
09	✓	✓	✓	✓	4.5	5.5	6.4	7.1	7.8	8.4	9.0	17.2	21	25	29	32	34
10	✓	✓	✓	✓	5.0	6.1	7.1	7.9	8.7	9.4	10.0	19.2	23	28	32	36	38
15	✓	✓	✓	✓	7.5	9.2	10.6	11.9	13.0	14.0	15.0	28	34	42	48	54	56
20	✓	✓	✓	✓	10.0	12.2	14.1	15.8	17.3	18.7	20	38	46	56	64	72	75
25	✓	✓	✓	✓	12.5	15.3	17.7	19.8	22	24	25	48	57	70	81	91	95
30	✓	✓	✓	✓	15.0	18.4	21	24	26	28	30	57	68	83	97	108	114
35	✓	✓	✓	✓	17.5	21	25	28	30	32	35	67	80	98	113	126	133
40	✓	✓	✓	✓	20	24	28	32	35	38	40	76	91	111	129	144	151
50	✓	✓	✓	✓	25	31	35	40	43	46	50	95	114	140	161	180	189
60	✓	✓	✓	✓	30	37	42	47	52	56	60	115	137	168	193	216	226

TABULATION IS BASED ON SPRAYING WATER AT TEMPERATURE OF 70° F (21° C)
 MORE CAPACITIES AVAILABLE ON REQUEST.