

TEKNOJET 2SC 400

EN 1829 - 2

RECOMMENDED FOR:
PROFESSIONAL WATER JET CLEANERS

RACCOMANDATO PER:
MACCHINE IDROPULTRICI PROFESSIONALI




Alternative versions:    

other colors available: BLUE, RED, GREY
altri colori disponibili: BLU, ROSSO, GRIGIO

Features:



Code	Hose size		Outside diameter		Max working pressure		Min burst pressure		Min bend radius		Weight		
	D.N.	Inch	mm	Inch	mm	PSI	Bar	PSI	Bar	Inch	mm	Lb/ft	kg/mt
TJ2SC04	6	1/4"	6,4	0,53	13,4	5800	400	23200	1600	2,95	75	0,18	0,27
TJ2SC05	8	5/16"	7,9	0,59	15,0	5800	400	23200	1600	3,34	85	0,22	0,32
TJ2SC06	10	3/8"	9,5	0,67	17,0	5800	400	23200	1600	3,54	90	0,27	0,40
TJ2SC08	12	1/2"	12,8	0,8	20,4	5800	400	23200	1600	5,11	130	0,36	0,54


TeknoJET 2SC 3/8" (9,5mm) EN 1829-2 -10°C / +150°C 14°F / +302°F 400 Bar 40 MPa **5800 Psi**

MARKING/MARCATURA: TRANSFER TAPE

OPERATING

TEMPERATURE RANGE:

- 10°C/+135°C
(14°F to +275°F)
with peak of +150°C (302°F)

TEMPERATURA DI ESERCIZIO:

- 10°C/+135°C
(14°F / +275°F)
con punte di +150°C (302°F)

TUBE:

hot water, detergent and oil synthetic rubber

SOTTOSTRATO:

gomma sintetica resistente a acqua calda, detersivi e oli

REINFORCEMENT:

2 high tensile steel braids

RINFORZO:


2 trecce di acciaio ad alto carico

COVER:

synthetic rubber with extreme abrasion resistance

COPERTURA:

gomma sintetica con estrema resistenza all'abrasione

Note: TO ORDER BLU VERSION PLEASE ADD "B" TO THE CODE
TO ORDER RED VERSION PLEASE ADD "R" TO THE CODE
TO ORDER GREY VERSION PLEASE ADD "G" TO THE CODE
TO ORDER FOREVER VERSION  PLEASE ADD "FV" TO THE CODE