

# S 3001 - SPEEDY - F1

Compressori d'aria  
coassiali  
*Direct driven air  
compressors*



## S 3001 - SPEEDY - F1

Tipo/Type	Volt/Hz	I	dB (A)	ℓ/min	C.F.M.	m³/h	Cil./St.	bar	psi	INPUT Watt	€/l'	Kg	m³
<b>S 3001/6 OL</b>	230/50/1	6	69	160	5.7	9,6	1/1	8	116	1100	3000	11	0.073
<b>S 3001/24 OL</b>	230/50/1	24	69	160	5.7	9,6	1/1	8	116	1100	3000	20	0.100
<b>SPEEDY 24 OL</b>	230/50/1	24	78	170	5.8	9,8	1/1	8	116	1300	2850	22	0.100
<b>F1 24</b>	230/50/1	24	79	190	6.7	11,4	1/1	8	116	1300	2850	25	0.100
<b>F1 24/2</b>	230/50/1	24	79	240	8.5	14,4	1/1	8	116	1700	2850	26	0.100
<b>F1 50</b>	230/50/1	50	79	190	6.7	11,4	1/1	8	116	1300	2850	44	0.196
<b>F1 50/2</b>	230/50/1	50	79	240	8.5	14,4	1/1	8	116	1700	2850	45	0.196
<b>F1 50/2,5</b>	230/50/1	50	80	250	8.8	15	1/1	10	145	1850	2850	46	0.196
<b>F1 100/2</b>	230/50/1	100	79	240	8.5	14,4	1/1	8	116	1700	2850	62	0.400
<b>F1 100/2,5</b>	230/50/1	100	80	250	8.8	15	1/1	10	145	1850	2850	63	0.400

# SPIDER

Compressori d'aria con trasmissione  
a cinghia e cilindro in ghisa  
*Belt driven air compressors  
with cast iron cylinder*



## SPIDER

Tipo/Type	Volt/Hz	I	dB (A)	ℓ/min	C.F.M.	m³/h	Cil./St.	bar	psi	INPUT Watt	€/l'	Kg	m³
<b>FB 50-2 SPIDER</b>	230/50/1	50	72	250	8.8	15	2/1	10	145	2	1240	50	0.263
<b>FB 100-2 SPIDER</b>	230/50/1	100	72	250	8.8	15	2/1	10	145	2	1240	62	0.393
<b>FB 150-2 SPIDER</b>	230/50/1	150	72	250	8.8	15	2/1	10	145	2	1240	86	0.831
<b>FB 200-2 SPIDER</b>	230/50/1	200	72	250	8.8	15	2/1	10	145	2	1240	100	1.128
<b>FB 100-3 SPIDER</b>	230/50/1	100	74	330	11.6	19,8	2/1	10	145	3	1600	64	0.393
<b>FB 150-3 SPIDER</b>	230/50/1	150	74	330	11.6	19,8	2/1	10	145	3	1600	88	0.831
<b>FB 200-3 SPIDER</b>	230/50/1	200	74	330	11.6	19,8	2/1	10	145	3	1600	102	1.128

\* Disponibile versione Volt 400/50/3 - Volt 400/50/3 available upon request