

PETROL HOSE COUPLINGS



MALE PART WITH THREADED FERRULE

| For hose mm | Male thread connection side | Male thread hose side DIN 13 | Female thread ferrule DIN 13 | Material | Weight/pc Kg | Reference |
|-------------|-----------------------------|------------------------------|------------------------------|----------|--------------|-----------|
| 13 x 4 | R 1/2, BSPT | M16 x 1.0 | | Brass | 0.13 | BPK11304T |
| 13 x 5 | R 1/2, BSPT | M 16 x 1.0 | | Brass | 0.13 | BPK11305T |
| 15 x 5 | R 3/4, BSPT | M 19 x 1.0 | | Brass | 0.19 | BPK11505T |
| 19 x 4 | R 3/4, BSPT | M 22 x 1.5 | | Brass | 0.16 | BPK11904T |
| 19 x 5 | R 3/4, BSPT | M 22 x 1.5 | | Brass | 0.17 | BPK11905T |
| 19 x 6 | R 3/4, BSPT | M 22 x 1.5 | | Brass | 0.20 | BPK11906T |
| 25 x 5 | R 1, BSPT | M 28 x 1.5 | | Brass | 0.25 | BPK12505T |
| 25 x 6 | R 1, BSPT | M 28 x 1.5 | | Brass | 0.27 | BPK12506T |
| 13 x 4 | G 1/2, BSP | M16 x 1.0 | | Brass | 0.13 | BPK11304 |
| 13 x 5 | G 1/2, BSP | M 16 x 1.0 | | Brass | 0.13 | BPK11305 |
| 15 x 5 | G 3/4, BSP | M 19 x 1.0 | | Brass | 0.19 | BPK11505 |
| 19 x 4 | G 3/4, BSP | M 22 x 1.5 | | Brass | 0.16 | BPK11904 |
| 19 x 5 | G 3/4, BSP | M 22 x 1.5 | | Brass | 0.17 | BPK11905 |
| 19 x 6 | G 3/4, BSP | M 22 x 1.5 | | Brass | 0.20 | BPK11906 |
| 25 x 5 | G 1, BSP | M 28 x 1.5 | | Brass | 0.25 | BPK12505 |
| 25 x 6 | G 1, BSP | M 28 x 1.5 | | Brass | 0.27 | BPK12506 |
| 13 x 4 | 1/2, NPT | M16 x 1.0 | | Brass | 0.13 | BPK11304N |
| 13 x 5 | 1/2, NPT | M 16 x 1.0 | | Brass | 0.13 | BPK11305N |
| 15 x 5 | 3/4, NPT | M 19 x 1.0 | | Brass | 0.19 | BPK11505N |
| 19 x 4 | 3/4, NPT | M 22 x 1.5 | | Brass | 0.16 | BPK11904N |
| 19 x 5 | 3/4, NPT | M 22 x 1.5 | | Brass | 0.17 | BPK11905N |
| 19 x 6 | 3/4, NPT | M 22 x 1.5 | | Brass | 0.20 | BPK11906N |
| 25 x 5 | 1, NPT | M 28 x 1.5 | | Brass | 0.25 | BPK12505N |
| 25 x 6 | 1, NPT | M 28 x 1.5 | | Brass | 0.27 | BPK12506N |



Male thread connection side: EN 10226-1, BSPT
 EN ISO 228-1, BSP; ANSI B 1.20.1, NPT
 Male thread hose side: ISO metric DIN 13
 Female thread ferrule: ISO metric DIN 13
 Other dimensions available on request

FEMALE PART WITH THREADED FERRULE

| For hose mm | Female thread nut | Male thread hose side DIN 13 | Female thread ferrule DIN 13 | Material | Weight/pc Kg | Reference |
|-------------|-------------------|------------------------------|------------------------------|----------|--------------|-----------|
| 13 x 4 | G 1/2, BSP | M 16 x 1.0 | | Brass | 0.13 | BPK21304 |
| 13 x 5 | G 1/2, BSP | M 16 x 1.0 | | Brass | 0.13 | BPK21305 |
| 15 x 5 | G 3/4, BSP | M 19 x 1.0 | | Brass | 0.14 | BPK21505 |
| 19 x 4 | G 3/4, BSP | M 22 x 1.5 | | Brass | 0.15 | BPK21904 |
| 19 x 5 | G 3/4, BSP | M 22 x 1.5 | | Brass | 0.16 | BPK21905 |
| 19 x 6 | G 3/4, BSP | M 22 x 1.5 | | Brass | 0.19 | BPK21906 |
| 25 x 5 | G 1, BSP | M 28 x 1.5 | | Brass | 0.21 | BPK22505 |
| 25 x 6 | G 1, BSP | M 28 x 1.5 | | Brass | 0.23 | BPK22506 |



Female thread connection side: EN ISO 228-1, BSP
 Male thread hose side: ISO metric DIN 13
 Female thread ferrule: ISO metric DIN 13
 Thread seal: PU
 Other dimensions available on request

PETROL HOSE COUPLINGS



THREAD SEAL - PUR

| ND | Inch | ODØmm | ID Ø mm | Height mm | Weight/pc kg | Reference |
|----|------|-------|---------|-----------|-----------------|-----------|
| 15 | 1/2" | 20.0 | 13.0 | 1.5 | 0.001 | X2RV013 |
| 20 | 3/4" | 26.0 | 19.0 | 1.5 | 0.001 | X2RV020 |
| 25 | 1" | 33.0 | 24.0 | 2.0 | 0.001 | X2RV025 |

Material: PU
 Colour: Brown
 Seal dimensions in compliance with EN 14420-5
 See chapter E for more information regarding chemical resistance



ACCESSORIES

WRENCH

| ND | Material | Weight/pc Kg | Reference |
|----------|----------|-----------------|-----------|
| 15-20-25 | Brass | 0.06 | BPKEY1 |

