



OUTSIDE
SKIVE



BXS



BXSH

OUTSIDE
SKIVE

RUBBER HOSES STEEL WIRE SPIRAL - TUBI GOMMA SPIRALATI ACCIAIO

Hose Size			ISO 3862 4SP			ISO 3862 4SH**			ISO 3862 R12 SAE100 R12									Collapse control mandrel Spina controllo collasso				
			Ferrule Boccola	Skiving length Lungh. di pelatura	Ø Swage (Ref.) Ø Press. (Rif.)	Ferrule Boccola	Skiving length Lungh. di pelatura	Ø Swage (Ref.) Ø Press. (Rif.)	Ferrule Boccola	Skiving length Lungh. di pelatura	Ø Swage (Ref.) Ø Press. (Rif.)	Ferrule Boccola	Skiving length Lungh. di pelatura	Ø Swage (Ref.) Ø Press. (Rif.)	Ferrule Boccola	Skiving length Lungh. di pelatura	Ø Swage (Ref.) Ø Press. (Rif.)		Ferrule Boccola	Skiving length Lungh. di pelatura	Ø Swage (Ref.) Ø Press. (Rif.)	
DN	Inch	Dash	Part.N.	mm	mm	Part.N.	mm	mm	Part.N.	mm	mm	Part.N.	mm	mm	Part.N.	mm	mm	Part.N.	mm	mm	Part.N.	
6,3	1/4"	-04	BXS04	18	19,0																	SCP04
10	3/8"	-06	BXS06	22	23				BXS06	22	22,7											SCP06
12,5	1/2"	-08	BXS08	24	26,7				BXS08	24	26,4											SCP08
16	5/8"	-10	BXS10	27	30,7				BXS10	27	30,6											SCP10
19	3/4"	-12	BXS12	30	34,4	BXS12	30	34,0	BXS12	30	33,2											SCP12
25	1"	-16	BXS16	38	42	BXS16	38	41,8	BXS16	38	41,4											SCP16
31,5	1 1/4"	-20	BXS20	45	51	BXSH20	45	48,8	BXS20	45	49,9											SCP20
38	1 1/2"	-24	BXS24	50	60	BXSH24	50	57	BXS24	50	58,8											SCP24
51	2"	-32	BXS32	55	74	BXSH32	55	70,7	BXSH32	55	71,1											SCP32

** The application of "CX" series hose fittings must be limited to the "ISO 3862 4SP" maximum working pressure.

** L'applicazione dei raccordi per tubo flessibile serie "CX" deve essere limitata alla massima pressione di esercizio del tubo "ISO 3862 4SP".