



# TSS

## Breather plug with valve

- ▶ Breather plug with galvanized-steel cover and specially-designed internal valve with an inox spring, calibrated from 0,05 to 0,10 bar, which opens at intervals to vent internal pressure created by fluid turbulence and keep out foreign bodies.
- ▶ It is especially recommended for applications on **Speed-shift Gears, Agricultural over-Gears and Industrial Speed-Reduction Gearboxes.**


[PRINTING NOTES](#)
[PRINT](#)

TYPE	CODE	GAS	d	h	f	e
TSS0G	1GTSS00M	1/8"	16,5	16	8	14
TSS1G	1GTSS10M	1/4"	16,5	17	9,5	17
TSS2G	1GTSS20M	3/8"	22	19	11	22
TSS3G	1GTSS30M	1/2"	26	20	11	27
TSS4G	1GTSS40M	3/4"	30	24	12	32
TSS5G	1GTSS50M	1"	38	29	14	40

TYPE	CODE	MB series	d	h	f	e
TSS0M	1MTSS00M	10 x 1	16,5	16	8	14
TSS1M	1MTSS10M	14 x 1,5	16,5	17	9,5	17
TSS2M	1MTSS20M	16 x 1,5	22	19	11	22
TSS3M	1MTSS30M	18 x 1,5	22	19	11	22
TSS4M	1MTSS40M	20 x 1,5	24	20	11	24
TSS5M	1MTSS50M	22 x 1,5	26	20	11	27
TSS6M	1MTSS60M	24 x 2	30	24	12	30
TSS7M	1MTSS70M	30 x 2	30	25	14	36
TSS8M	1MTSS80M	33 x 2	38	29	14	40