

# Pacer™



## Product Specifications

### Application

For all types of gasoline dispensing applications where flexibility and a lightweight hose is desired. Pacer™ is designed with a spiral textile reinforcement. UL 330 and CUL approved.

### Construction Tube

Nitrile synthetic rubber (ORS)

### Cover

Chemivic™ synthetic rubber (ORS)

### Reinforcement

Spiral synthetic yarn with static wire

### Temperature Range

-40°F to 140°F (-40°C to 60°C)

### Packaging

Reels or coupled lengths

### Branding

Example: 3/4" Pacer™ Continental ContiTech

### Couplings

Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

### Order Codes

Available in bulk and coupled assemblies.

## Pacer™

ID		Nom. OD		Weight	
in.	mm	in.	mm	lb./ft.	kg/m
5/8	15.9	0.98	24.9	0.28	0.42
3/4	19.1	1.15	29.2	0.37	0.55
1	25.4	1.50	38.1	0.60	0.89

**Air & Multipurpose**

- General Purpose
- Heavy Duty
- Push-on

Chemical Transfer

Cleaning Equipment

- Food**
- Transfer
- Washdown

Marine

**Material Handling**

- Abrasives
- Bulk Transfer
- Cement & Concrete

Mining

**Petroleum**

- Aircraft Fueling
- Dispensing
- Dock Transfer

Spray

Steam

Vacuum

LPG Delivery

**Water**

- Discharge
- Suction & Discharge
- Washdown

Welding

Coupling Systems

Equipment

Appendix