

For the SWIVELLING version add the suffix "/SO" at the P/N, except for the 560 series.  
For example:  
430/60/SO

**FIXED PAINTED STEEL**

**FIXED S. STEEL AISI 304**

**Supplied with:**

- hose in antistatic EPDM black synthetic rubber with galvanized steel coupling
- brass swivel joint
- "Viton" seals
- central shaft in galvanized steel or stainless steel
- inlet hose 0,6 m to connect the hose reel to the system (standard on the versions with hose)



	P/N	P/N	Hose supplied	Connection	
				Inlet	Outlet
S. 430	430/60	-	without hose*	F 1/2"G	M 1/2"G
	430/61	-	10m 5/8" (968/20)	F 3/4"G	M 3/4"G
	430/62	-	8m 3/4" (968/25)	F 3/4"G	M 3/4"G
S. 4430 ABS	4430/60	-	without hose*	F 1/2"G	M 1/2"G
	4430/61	-	10m 5/8" (968/20)	F 3/4"G	M 3/4"G
	4430/62	-	8m 3/4" (968/25)	F 3/4"G	M 3/4"G
S. 530	530/60	-	without hose*	F 1"G	F 1"G
	530/63	-	12m 19x27 (978/12)	F 1"G	M 3/4"G
	530/64	-	8m 25x35 (988/8)	F 1"G	M 1"G
S. 540	540/10	542/10	without hose*	F 1"G	F 1"G
	540/61	542/61	15m 19x27 (978/15)	F 1"G	M 3/4"G
	540/62	542/62	20m 19x27 (978/20)	F 1"G	M 3/4"G
	540/63	542/63	15m 25x35 (988/15)	F 1"G	M 1"G
S. 560	560/10	562/10	without hose*	F 1"G	F 1"G
	560/63	562/63	40m 19x27 (978/40)	F 1"G	M 3/4"G
	560/64	562/64	20m 25x35 (988/20)	F 1"G	M 1"G
	560/65	562/65	30m 25x35 (988/30)	F 1"G	M 1"G

\* for the version without hose the maximum work pressure is 20 bar



Atex 94/9

- ▶ II 3GD c X (per serie 4430 ABS)
- ▶ IIB 2GD c T4 T135°C X

## AD blue 10 bar

For the SWIVELLING version add the suffix "/SO" at the P/N.  
For example:  
436/20/SO

**FIXED PAINTED STEEL**

**FIXED S. STEEL AISI**

**Supplied with:**

- hose in antistatic EPDM rubber with AISI 304 stainless steel coupling
- AISI 304 - 316L stainless steel swivel joint
- "Viton" seals
- central shaft in stainless steel AISI 304
- inlet hose 0,6 m to connect the hose reel to the system (standard on the versions with hose)



	P/N	P/N	Fluid contact parts	Hose supplied	Connection	
					Inlet	Outlet
S. 436	436/20	-	AISI 316L	without hose*	F 1"G	F 3/4"G
S. 436	436/250	-	AISI 304	without hose*	F 3/4"G	F 3/4"G
	436/251	-	AISI 304	10m 19x27 (882/10)	F 3/4"G	M 3/4"G
	436/252	-	AISI 304	15m 19x27 (882/15)	F 3/4"G	M 3/4"G
S. 4436 ABS	4436/20	-	AISI 304	without hose*	F 1/2"G	F 1/2"G
	4436/21	-	AISI 304	8m 19x27 (882/8)	F 3/4"G	M 3/4"G
S. 537	-	537/20	AISI 316L	without hose*	F 1"G	F 3/4"G
S. 537	-	534/250	AISI 304	without hose*	F 1"G	F 1"G
	-	537/251	AISI 304	10m 19x27 (882/10)	F 3/4"G	M 3/4"G
	-	537/252	AISI 304	15m 19x27 (882/15)	F 3/4"G	M 3/4"G

\* for the version without hose the maximum work pressure is 20 bar



Atex 94/9

- ▶ II 3GD c X (per serie 4430 ABS)
- ▶ IIB 2GD c T4 T135°C X